

ESP Downhole Monitoring Systems

Predict ESP motor and cable run life by measuring ESP insulation resistance

ACE Downhole sensors are specifically designed for long life and accurate downhole pressure, temperature, and vibration delivery.



Downhole sensors

- High temperature, high pressure, and dual pressure models available
- 2 3/8-in. 8 RND EUE thread on the bottom of the sensor to mount any additional downhole components

 **30k+**
ACE Downhole sensors installed worldwide



Downhole sensors adaptors

- Most common sizes available for various ESP motor brands
- Available in carbon steel or stainless steel

2 
YEAR

warranty,
unmatched by
any competitor



Robust and
capable
of multiple
deployments



Surface readout units

- SRU2i includes ethernet and USB connectivity
- SRU3i connects directly to a Baker Hughes Advantage/GCS drive and provides WiFi



High-voltage interface

- Rated to 5,000 VAC and tested at 7,000 VAC
- NEMA 4, 4X, 12, 13 enclosure

Benefits

- Universal compatibility with all oil field submersible pump motors
- Predict and extend ESP run life by monitoring ESP insulation resistance
- Sustain uninterrupted downhole data in applications with unstable power

Product highlights

- Completely sealed and dry design
- Patented smart circuit to protect the sensor from high voltage, current overloads, and ground fault related failures



Installation and testing

- Hydraulic pressure test unit to enable system verification at surface before installation NEMA 4, 4X, 12, 13 enclosure
- Portable surface readout unit enables sensor testing without connecting to a power source
- ACE Spooler monitors ESP while running in hole and sends an alarm to personnel on the wellsite the moment ESP cable gets damaged

DOWNHOLE SENSORS

	ACE Single	ACE Dual
Intake Pressure Range	0-6,000 / 8,000 & 10,000 psi	0-6,000 / 8,000 & 10,000 psi
Intake Pressure Accuracy	+/- 0.1% Typical 0.2 FS	+/- 0.1% Typical 0.2 FS
Intake Pressure Resolution	0.1 PSI	0.1 PSI
Transducer Type	Digital Strain Gauge	Digital Strain Gauge
Discharge Pressure Range	N/A	0-6,000 / 8,000 & 10,000 psi
Discharge Pressure Accuracy	N/A	+/- 0.1% Typical 0.2 FS
Discharge Pressure Resolution	N/A	0.1 PSI
Intake Temperature Range	32 - 350°F, 0 - 177°C	32 - 350°F, 0 - 177°C
Intake Temperature Accuracy	3.5°F, 2°C	3.5°F, 2°C
Intake Temperature Resolution	1°F, SRU, 0.1°F, SRU2, 0.01°F, Spooler & SRU3i	1°F, SRU, 0.1°F, SRU2, 0.01°F, Spooler & SRU3i
Motor Winding Temp Resolution*	1°F, SRU, 0.1°F, SRU2, 0.01°F, Spooler & SRU3i	1°F, SRU, 0.1°F, SRU2, 0.01°F, Spooler & SRU3i
Vibration Range	0 - 10G	0 - 10G
Vibration Accuracy	0,50%	0,50%
Vibration Resolution	0,01G	0,01G
ESP Insulation Resistance	50kOhms - 60MOhms	50kOhms - 60MOhms
Maximum Motor Voltage	4160 VAC	4160 VAC
Physical Diameter	3.72 in. or 3.94 in.**	3.72 in. or 3.94 in.**
Physical Length	18.5 in.	23.0 in.
Physical Weight	42 lbs. 19 kG	44 lbs. 20 kG
Material	316 SS	316 SS
Motor Winding Temp Range*	32 - 600°F, 0 - 316°C	32 - 600°F, 0 - 316°C
Motor Winding Temp Accuracy*	3.5°F, 2°C	3.5°F, 2°C

*Available with RTD or Thermocouple interface
 **10 ksi is only available in 3.94 in. or 3.72 in. 1020 CS only

SURFACE READOUT UNITS

	SRU	SRU2i	SRU3i
Power	115VAC +/- 15% 50/60Hz	115 VAC for SRU2i 10-28 VDC 1A for SRU2i-DC	115 VAC for SRU3i 10-28 VDC 1A for SRU3i-DC
Display Type	6 digit Alpha Numeric LED	8 digit Alpha Numeric LED	-
Motor Controller Connection (Isolated)	iCON Series Interface. Support for legacy controllers (F3/F5 Commander series)	iCON Series Interface. Support for legacy controllers (F3/F5 Commander series) plus additional RS-485 Modbus port	Supports GCS Legacy CITbus & Advantage CITbus
Modbus RS-485 (Isolated)	3 wire standard	3 wire standard	3 wire standard
Modbus RS-232 (Isolated)	3 wire, no handshaking required	3 wire, no handshaking required	3 wire standard
USB Modbus (Isolated)	-	Standard USB 'B'	Standard USB-A
Ethernet Modbus (Isolated)	-	Standard CAT5E 8 Pin connector	-
WiFi Interface	-	-	Standard worldwide, license free 802.11 b/g/n
Analog Outputs (Isolated)	-	4x 0-20mA User configurable (SRU2 sources power)	-
Relay Outputs (Isolated)	-	2x Form C User configurable 240VAC / 8 Amps	-
SD Datalogger	-	Up to 32 GByte (SDHC mode supported)	-
Internal Memory (SRU2i version)	-	32 GByte	-
Operating Temperature	0 - 158°F, -18 - 50°C	0 - 158°F, -18 - 50°C	0 - 158°F, -18 - 50°C
Insulation Resistance	No	Yes	Yes
Dimensions	6.00 in. x 5.25 in. x 2.25 in.	9.50 in. x 5.75 in. x 1.75 in.	7.38 in. x 5.75 in. x 1.75 in.
Weight	1.5 lbs	2 lbs	2 lbs
UL Certification	Conforms to UL Std. 61010-1	Conforms to UL Std. 61010-1	Conforms to UL Std. 61010-1
CSA Certification	Certified to CAN/CSA Std. C22.2# 61010-1	Certified to CAN/CSA Std. C22.2# 61010-1	Certified to CAN/CSA Std. C22.2# 61010-1

ACE Downhole | T: +1 918-876-3246 | E: sales@acedownhole.com

This document is provided on an "as is" basis without warranties of any kind. ACE Downhole, LLC DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR SUITABILITY FOR ANY PURPOSE, TITLE, AND NON-INFRINGEMENT. While reasonable care has been taken in the preparation of this document, ACE Downhole, LLC does not represent or warrant that the contents of this document are accurate, complete, reliable, current or error-free.